



USES

- ❖ Recommended for floor and wall areas.
- ❖ Can be used for internal installation of ceramic tiles, granites & sandstone.
- ❖ Excellent bonding
- ❖ Recommended to use premium grade adhesives "Ceramix Premium" for installation of marbles and sandstone on heavy traffic areas, utility areas and wet areas.

ADVANTAGES

- ❖ Ceramix 2000 is a cement-based mortar.
- ❖ Can be used for internal installation of tiles.
- ❖ Specially formulated to suit for extreme working conditions.
- ❖ Excellent resistance to humidity

CHARACTERISTICS

Appearance	Powder
Colour	White or grey
Pot Life	30 minutes
Open Time	20 minutes (25°C)
Dry Density	1.4 kg / Ltr

CERAMIX 2000

CEMENTITIOUS TILE ADHESIVE

Ceramix 2000 ceramic tile adhesive for floor and wall applications.

Cement-based mortar for fixing ceramic tiles, granites and stones for interior applications.

Use premium grade Ceramix Premium series adhesives for specific installation of vitrified tiles, marbles and tiles for heavy traffic areas, utilities, and permanent wet areas.



STANDARDS

Ceramix 2000 Conforms to BS 5980 : 1980 and BS 1881 part 207 1992.

APPLICATION INSTRUCTIONS

Surface Preparation

The surface should be sound, clean, and free from dirt, oil or grease before Ceramix 2000 is applied. Pre soak the surface and do not allow pond the water on application areas.

MIXING

Mix Ceramix 2000 adhesive in a ratio of 6 litres of water per 25 kg bag, depending of working conditions. Keep it for approximately 3 minutes to fatten it. Recommended to use mixing pedal for homogenous mixing & better chemicals performance.

Apply Ceramix 2000 adhesive to a uniform thickness of 3 mm to 6 mm on the surface, working on an area of not more than 1m² at a time. For horizontal applications a solid bed fixing is recommended as well as for heavy-duty vertical applications. For other vertical applications use a toothed spatula to comb horizontally to remove excess. Apply the tile, press it, smooth out carefully so that the mortar is spread evenly. If the bonding is perfect, the tile will not slide. Approximately 3-4 kg/m² depending on the surface conditions. The joints can be filled with EUROBUILD EuroGrout series (available in grey, white or colours on request).

APPROX COVERAGE

Thin bed fixing : @ 3 mm 3-4 m²/25 kg Bag
Solid bed fixing : @ 5 mm 3-4 m²/25 kg Bag

Shelf Life

Ceramix 2000 has a shelf life of 12 months in unopened packs, if stored in a cool and dry place.

PACKING

Available in 20 & 25 Kg packs

Fire

Ceramix 2000 is non - flammable skin or eyes with fresh water immediately.

Points to be noted

The open time of Ceramix 2000 adhesive at 25oC is approximately 20 minutes. Therefore care should be taken in preparing the mortar. Prepare only the surface, which can be tiled within this time. Ceramix 2000 adhesive should not be used on painted or metal surfaces.





TECHNICAL SUPPORT

EUROBUILD offers a technical support package to specific end-users and contractors, as well as on-site technical assistance in locations.

HEALTH & SAFETY

All chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn. Treat any splashes to the skin or eyes with fresh water immediately.

Should any of the products be accidentally swallowed, do not induce vomiting, but all for medical assistance immediately. Ensure the pack is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling.

NOTE

The information supplied in our literature or given by our employees is based upon extensive experience and together with that supplied by our agents or distributors, is given in good faith in order to help you. Our company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

COMPLEMENTARY PRODUCTS

EUROBUILD manufactures a wide range of complementary products which includes:

- ❖ Waterproofing systems
- ❖ Cementitious additives
- ❖ Bonding Agent
- ❖ Concrete Flooring
- ❖ Self Levelling
- ❖ Concrete Structural Repair Products
- ❖ Marble and Stone protection sealers
- ❖ Tile Adhesive
- ❖ Tile Grouts
- ❖ Epoxy Tile Adhesive & Grouts
- ❖ Non Shrink Grouts
- ❖ Expansion Joint Sealants

Air conditioning canvas coating, Vapour barrier & Duct insulation adhesives.



PERFORMANCE FEATURES & BENEFITS

AVAILABLE COLORS

GRAY

WHITE

RECCOMENTED AREAS

DRY AREAS

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR



EXPOSED TO SUN

TILES



CERAMIC TILES



PORCELAIN TILES



MARBLE/STONE

SURFACES



FLOOR



WALL

APPLICATION DETAILS & SURFACE PREPARATION

MIXING DRILL



Stir well before use

TOOLS



Teeth Trowel

MIXING



Water

MIXING RATIO



Supplied Proportion

OPEN TIME



10 MIN 25 DEGREE

APPLICATION THICKNESS



Recomented Thickness
2-15 mm

APPLICATION ENVIRONMENT



Temperature:
5-40 Degree
Humidity : Below 80%

CLEANING



Clean the surface and the tools with clean water and wet cloth

SURFACE PREPARATION



Surface clean thoroughly, saturate with water prior to tile installation

APPLICATION



Reccomented for floor and wall

APPLICATION SURFACES



Concrete, precast, screed, rubber/cork sheets, gypsum board, plywood, silicate board etc.

VOC

LOW

MEDIUM

HIGH

PACKING



20 KG



25 KG