

PROUDI TRADING FZE

 Sharjah, Uae
  +971 67150164
 www.proudi.ae
  info@proudi.ae

PRODUCT DESCRIPTION:

Premium 2000 is a high-quality, cement-based mortar designed for fixing ceramic tiles, granites, and stones. It is part of the Ceramix Premium series and is ideal for use in demanding applications including heavy traffic areas, utilities, and permanent wet zones.

FEATURES AND BENEFITS:

- **Excellent Bonding:** Provides superior adhesion to various substrates, ensuring a long-lasting bond.
- **Resistance to Humidity:** Formulated to withstand high moisture conditions, making it suitable for wet areas.
- **Extreme Working Conditions:** Specially developed to perform reliably in challenging environments.
- **Versatile Application:** Suitable for both floor and wall installations.
- **Premium Grade Adhesive:** Designed for high-performance applications, including marbles and sandstone in areas of heavy traffic.

APPLICATION AREAS:

- Internal installations of ceramic tiles, granites, and sandstone.
- Heavy traffic areas.
- Utility areas.
- Permanent wet areas.
- **USAGE INSTRUCTIONS:**

PREMIUM 2000

PREMIUM TILE ADHESIVE FOR WALL & FLOOR

Prepare the substrate ensuring it is clean, dry, and free of contaminants.

Mix Premium 2000 with clean water to achieve a smooth, workable consistency.

Apply the adhesive to the substrate using a notched trowel.

Press tiles firmly into the adhesive, ensuring proper coverage and alignment.

Allow the adhesive to set as per the manufacturer's recommendations before grouting.

STORAGE AND SHELF LIFE:

Store in a dry place, off the ground, and in its original packaging.

Shelf life is approximately 12 months from the date of manufacture if stored under recommended conditions.

SAFETY PRECAUTIONS:

Use appropriate personal protective equipment (PPE) such as gloves and safety goggles.

Follow safety instructions provided on the product packaging and Safety Data Sheet (SDS).

CHARACTERISTICS

Appearance	Powder
Colour	White or grey
Pot Life	30 minutes
Open Time	20 minutes (250 C)
Dry Density	1.4 kg / Ltr



STANDARDS

PREMIUM 2000 Conforms to BS 5980 : 1980 and BS 1881 part 207 1992.

APPLICATION INSTRUCTIONS

Surface Preparation

The surface should be sound, clean, and free from dirt, oil or grease before PREMIUM 2000 is applied. Pre soak the surface and do not allow pond the water on application areas.

MIXING

Mix PREMIUM 2000 adhesive in a ratio of 6 litres of water per 25 kg bag, depending of working conditions. Keep it for approximately 3 minutes to fatten it. Recommended to use mixing pedal for homogenous mixing & better chemicals performance. Apply PREMIUM 2000 adhesive to a uniform thickness of 3 mm to 6 mm on the surface, working on an area of not more than 1m² at a time. For horizontal

Bed fixing is recommended for heavy-duty vertical applications. For other vertical applications, use a toothed spatula to

comb horizontally to remove excess. Apply the tile, press it, smooth out carefully so that the mortar is spread evenly. If the bonding is perfect, the tile will not slide. Approximately 3-4 kg/m² depending on the surface conditions. The joints can be filled with PROUDI PROUDIGROUT series (available in grey, white or colours on request).

APPROX COVERAGE

- Thin Bed Fixing: Apply at a thickness of 3 mm. Coverage is approximately 3-4 m² per 25 kg bag.
- Solid Bed Fixing: Apply at a thickness of 5 mm. Coverage is approximately 3-4 m² per 25 kg bag.

PACKING

Available in 20 & 25 Kg packs

Fire

PREMIUM 2000 is non - flammable skin or eyes with fresh water immediately.

Points to be noted

The open time of PREMIUM 2000 adhesive at 25°C is approximately 20 minutes. Therefore care should be taken in preparing the mortar. Prepare only the surface, which can be tiled within this time. PREMIUM 2000 adhesive should not be used on painted or metal surfaces.

