

Material Safety Data Sheet



SADAF HYDRATED LIME CO.

CHEMICAL DATA

Formula for Sadaf Hydrated Lime:

Sadaf Hydrated Lime consists of calcium hydroxide combined with small amounts of magnesium hydroxide and silica.

Calcium hydroxide is manufactured by mixing calcium oxide (burnt lime) with water in a reaction vessel, and sizing via separators.

HAZARDS IDENTIFICATION

Not classified as a dangerous good according to NZS 5433.

UN No. None Allocated

Hazchem Code None Allocated

HASNO Classes 8.2C, 8.3A, 9.1D

HASNO Approval No. 002925

PHYSICAL DATA

Appearance and Odour:

White fine crystalline powder; no odour

Boiling Point:

Not applicable, product is a powdered solid

Melting Point:

Not applicable, product is a powdered solid

Vapour Pressure:

Not applicable, product is a powdered solid

Bulk Density:

0.45 – 0.65 tonnes/cubic metre

pH:

12.2 at 20°C

STABILITY AND REACTIVITY

Stability:

Product is stable. Keep dry until used.

Incompatibility:

Will react violently with maleic anhydride, nitroethane, nitromethane, nitroparaffins, nitropropane and phosphorous. Toxic products are produced from reaction with polychlorinated phenols and potassium nitrate.

FIRE FIGHTING MEASURES

Hydrated Lime is non-flammable and non-explosive. No hazardous decomposition products are expected during normal use of this product. Hazardous polymerisation will not occur.

HEALTH HAZARD DATA

Acute:

Hydrated Lime can dry the skin and cause caustic burns. Direct contact with the eyes can cause severe irritation, exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage. Inhalation can irritate the upper respiratory system causing coughing, and bronchitis at high levels. Ingestion by swallowing may result in ulceration-burns to the mouth and throat, nausea, vomiting, abdominal pain and diarrhoea.

Chronic:

Chronic respiratory effects are not expected to occur with over exposure at high levels due to the immediate irritant and/or corrosive effects. Hypersensitive individuals may develop allergic dermatitis.

This product contains small amounts of crystalline silica. Long-term exposure to crystalline silica causes silicosis, a form of pulmonary fibrosis. Continued exposure to crystalline silica can lead to cardiopulmonary impairment. Symptoms are usually delayed (10 years or more).



SADAF HYDRATED LIME CO.

EXPOSURE CONTROLS/PERSONAL PROTECTION INFORMATION

| Name | Formula | CAS number | Proportion | NZ-WES-TWA |
|---------------------|---------------------|------------|------------|---|
| Calcium Hydroxide | Ca(OH) ₂ | 1305-62-0 | 93% | 5mg/m ³ as inspirable dust |
| Magnesium Hydroxide | Mg(OH) ₂ | 1309-42-8 | 1% | 10mg/m ³ as inspirable dust 3mg/m ³ as respirable dust |
| Quartz | SiO ₂ | 14808-60-7 | 0.4% | 0.2mg/m ³ as respirable dust |

Respiratory Protection:

In dusty environments, an approved Class P1 or P2 particulate respirator is recommended.

Ventilation:

An exhaust fan deducted from near point of generation can be used to control airborne dust levels. Dust levels and other discharge of dust should comply with Health and Safety in Employment Legislation, Resource Consents and any relevant District or Regional rules.

Eye Protection:

Use tight fitting goggles or protective eyewear in dusty environments.

Skin Protection:

Use barrier creams, impervious, abrasion and alkali resistant gloves, boots, and protective clothing to protect the skin from prolonged contact with wet dust. Immediately after working with wet dust, workers should shower with soap and water.

EMERGENCY AND FIRST AID PROCEDURES

Pour clean water into eyes for at least 15 minutes and seek prompt medical attention; wash exposed skin areas with soap and plenty of water. If irritation develops seek medical attention; if ill effects due to inhalation, move person to fresh air. Keep warm, quiet and seek medical attention.

SPILL PROCEDURES

Steps to be taken in case material is spilled: Use dry clean up methods that do not disperse dust into the air. Avoid inhalation of dust and contact with skin. Emergency procedures are not required.

Disposal Method:

Small amounts of material can be disposed of as common waste or returned to the container for later use if not contaminated.

Large amounts may require special handling. Material should be kept out of storm water and sewer drains. Any discharge during clean up should comply with any relevant District or Regional Council requirements.

STORAGE AND HANDLING

The material should be kept free from moisture until used. Normal temperatures and pressures do not affect the material. Promptly remove dusty clothing or clothing which is wet with reject hydrate fluids and launder before reuse. Wash thoroughly after exposure to dust or wet reject hydrate mixtures or fluids.

NOTE: THIS MATERIAL SAFETY DATA SHEET ATTEMPTS TO DESCRIBE AS ACCURATELY AS POSSIBLE THE POTENTIAL EXPOSURES ASSOCIATED WITH NORMAL LIME USE. HEALTH AND SAFETY PRECAUTIONS IN THE DATA SHEET MAY NOT BE ADEQUATE FOR ALL INDIVIDUALS AND/OR SITUATIONS. USERS HAVE THE RESPONSIBILITY TO EVALUATE AND USE THIS PRODUCT SAFELY AND TO COMPLY WITH ALL APPLICABLE LAWS AND REGULATIONS. IF UNSURE OF ITS CURRENCY PLEASE CONTACT Sadaf Hydrated LIME.