

DREAM HOME INNOVATION (FZE)

دریم هوم اینوفیشن م.م.ح

BLOCKB-B24-025 SHARJAH UAE. TRN: 104126032200003



PROPERTIES

- ✓ Compatible to a wide range of surfaces
- ✓ Non flammable and non hazardous
- ✓ Solvent-free
- ✓ Shrink proof and long lasting
- ✓ Resistant to mechanical and thermal stress
- ✓ High initial tack and final bond strength
- ✓ Low emissions of **VOC**
- ✓ Suitable for under wall coverings
- ✓ Excellent Antifungal characteristics
- ✓ Eco friendly and non toxic

COVERAGE

| | |
|--------------|-----------------------------|
| Notch A2 | Approx. 6m ² /Kg |
| Open time | Approx. 15-25 min |
| Working time | Approx. 35 minutes |
| Load bearing | Approx. 24 hours |

EUROBOND WPA 666

Wall Paper Bond Adhesive

Premixed synthetic resin based wall paper adhesive. Specially formulated for use with nonwoven and vinyl backed wall papers. It has antifungal characteristics to protect fungal

Specialty synthetic resin dispersion adhesive compound for bonding wall coverings



DREAM HOME INNOVATION (FZE)

دریم هوم اینوفیشن م.م.ح

BLOCKB-B24-025 SHARJAH UAE. TRN: 104126032200003

TECHNICAL INFORMATION

| | |
|------------------|------------------------------|
| Base Material | Specialty synthetic Emulsion |
| Appearance | White paste |
| Consistency | High viscous |
| Open time | Approx 4-5 hours. |
| Specific gravity | Approx. 1 kg/l m +/- 0.05 |
| PH @25 °C | 4-5 |
| Durability VOC | Excellent |
| Toxic | Low, Green Product |
| | Nil |

TEMPERATURE RESISTANCE

Storage 0 °C to 45 °C, protect from frost storage
Cleanable Clean before the initial setting

Storage 12 months, cool and dry
Packaging 10 & 15 kg plastic bucket

The above times are based on normal climatic conditions (32 °C / 55% rel. humidity).

PRODUCT SAFETY

EuroBond WPA 666 is synthetic based. No special safety procedures or measures are necessary for its use.

SUBSTRATE PREPARATION

Substrates must be level and clean thoroughly. Any loose particles and dust must be vacuumed and removed. Recommended to use wet cloth and clean the surface prior to the adhesive application. Free from structural defects, firm, damp, dry and free of substances which may impair adhesion. Prepare the substrate with suitable that it is ready to receive wall coverings. Wall must be dust & dirt free prior to the adhesive application.

IMPORTANT INFORMATION

– Do not install coverings at wall temperatures below 10 °C and a relative humidity > 75 %.

–Remove any skin of dried-up adhesive which may have formed (due to improper storage).

–Immediately remove fresh spots of adhesive with a moist cloth. Tools and equipment clean with water.

–Tightly close opened buckets and use them up as soon as possible.

Open and working time may vary depending on temperature, relative humidity and absorbency of the substrate. They will be shorter at higher temperatures and lower humidity, but longer at lower temperatures, higher humidity and with nonabsorbent substrates.



DREAM HOME INNOVATION (FZE)

دریم هوم اینوفیشن م.م.ح

BLOCKB-B24-025 SHARJAH UAE. TRN: 104126032200003

APPLICATION

Stir the adhesive well prior to apply and evenly spread to the substrate with a brush/roller. Depending on the backing structure, apply the adhesive. Immediately install the coverings.

Avoid air pockets and carefully rub the covering down to ensure good wetting of the back. The covering material must be free of tension and lie flat on the substrate.

INFORMATION

Do not dispose of the product into natural dewater systems. Drains or the soil. Recycle empty containers (drip free and open). All chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instructions). Treat any splashes to the skin or eyes with fresh water immediately. Call for medical assistance immediately.

NOTE

The information supplied in our literature or given by our employees is based upon extensive experience and, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

PRODUCTS RANGE

- Water Proofing Systems
- Additives
- Bonding Agent
- Concrete Flooring Hardener
- Self Levelling Systems
- Epoxy Floor Coating
- Polyurethane Floor Coating
- Polyurethane Injection
- Concrete Structural Repair Products
- Marble and stone protection system
- Cementitious & Epoxy Grouts
- Aiconditioning Canvas, Vapour Barrier Coating & Duct Insulation coating.

